

KM-EMV


- Counternut with cutting edges for secure fixing of EMC cable glands
- for cutting through painted surfaces to ensure optimum contact with equipotential bonding
- increased vibration resistance

Material

Brass, nickel plated

Technical data

Temperature range: up to +200°C



Dimensions

G Thread size inside
SW Spanner size

metric thread - female

Part no.	Size Metr.	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
90165	M12 x 1,5	15,0	100	o. r.	o. r.	o. r.
90166	M16 x 1,5	19,0	100	o. r.	o. r.	o. r.
90167	M20 x 1,5	24,0	100	o. r.	o. r.	o. r.
90168	M25 x 1,5	30,0	100	o. r.	o. r.	o. r.
90169	M32 x 1,5	36,0	100	o. r.	o. r.	o. r.
90170	M40 x 1,5	46,0	50	o. r.	o. r.	o. r.
90171	M50 x 1,5	60,0	50	o. r.	o. r.	o. r.
90172	M63 x 1,5	70,0	25	o. r.	o. r.	o. r.

metric thread - female - KM-EMV-XXL - for large cable diameters

Part no.	Size Metr.	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
99875	M72 x 2,0	80,0	1	o. r.	o. r.	o. r.
93209	M75 x 1,5	80,0	1	o. r.	o. r.	o. r.
98698	M80 x 2,0	95,0	1	o. r.	o. r.	o. r.

PG thread - female

Part no.	Size PG	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
97243	7	15,0	100	o. r.	o. r.	o. r.
97244	9	18,0	100	o. r.	o. r.	o. r.
97166	11	21,0	100	o. r.	o. r.	o. r.
97167	13,5	23,0	100	o. r.	o. r.	o. r.
97168	16	26,0	100	o. r.	o. r.	o. r.
97169	21	32,0	100	o. r.	o. r.	o. r.
97170	29	41,0	50	o. r.	o. r.	o. r.
97171	36	51,0	25	o. r.	o. r.	o. r.
97245	42	60,0	25	o. r.	o. r.	o. r.
97246	48	64,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request